



### KEY FEATURES

Trimble R-Track technology for comprehensive GNSS support

A modular system with external antenna for maximum flexibility

Advanced receiver technology and proven system design combined

An important component of the Trimble Connected Site



The Trimble® R7 GNSS System is a multi-channel, multi-frequency GNSS (Global Navigation Satellite System) receiver and UHF radio combined in one exceptionally rugged unit. The Trimble R7 GNSS combines advanced receiver technology with proven system design to provide maximum flexibility, accuracy, and productivity.

#### TRIMBLE R-TRACK TECHNOLOGY FOR COMPREHENSIVE GNSS SUPPORT

Powered by the enhanced RTK engine, Trimble R-Track™ technology in the Trimble R7 GNSS supports the GPS Modernization signals L2C and L5, as well as GLONASS.

Its ability to track more satellites—both GPS and GLONASS—means Trimble R-Track can help to improve field productivity, and the resulting postprocessed or RTK solution is enhanced. The new and coming L2C and L5 will also improve the solution, plus these signals are more easily acquired and tracked in challenging GPS conditions.

Investing in the power of Trimble R-Track prepares you for future GNSS capabilities. Trimble, already proven in GPS, will continue to lead in additional GNSS support<sup>1</sup>.

#### PROVEN SYSTEM DESIGN

The overall design of the Trimble R7 GNSS system has been tried, tested, and proven in the field.

#### FLEXIBLE SEPARATE ANTENNA OPTIONS

Use the Trimble® Zephyr Geodetic™ 2 ground plane antenna<sup>2</sup> to minimize signal multipath at the Trimble R7 GNSS base, providing the “cleanest” data.

As a rover, the modular Trimble R7 GNSS with Trimble Zephyr 2 antenna is extremely flexible: Carry the receiver on the pole, wear it in the purpose-built Trimble backpack, or drive with the Trimble R7 GNSS inside your vehicle. The Trimble R7 GNSS supports the way you want to work.

#### NEW BLUETOOTH WIRELESS COMMUNICATION

For extra convenience and fewer cable hassles, the Trimble R7 GNSS includes Bluetooth for wireless connection to a Trimble controller, such as the Trimble® TSC2® Controller.

#### Exceptionally Rugged and Lightweight

The GNSS receiver and internal UHF radio are fully protected from water, dust, and shock inside the unit's full metal jacket. This field sturdiness makes the Trimble R7 GNSS ideal for tough environments.

#### THE ORIGINAL INTEGRATED SURVEYING SOLUTION AND BEYOND

The Trimble R7 GNSS system is designed to support Trimble's original Integrated Surveying™ solution. Combine your GPS and optical data in one job file in powerful Trimble field software such as Trimble Survey Controller™, then transfer the job file seamlessly to your Trimble office software, such as Trimble® Business Center, for processing.

Whenever you're facing a new surveying challenge, your partnership with Trimble places the right tools and techniques, including GNSS technology, at your fingertips. Each Trimble system seamlessly integrates via shared workflows and technologies, making your everyday job site a place where the whole is greater than the sum of its parts: **Welcome to the Connected Site.**

<sup>1</sup> Trimble research and development divisions are already working closely with Galileo satellite system teams to ensure delivery of the benefits of this new GNSS in advance of the system being operational.

<sup>2</sup> The Trimble Zephyr Geodetic 2 antenna supports GPS, GLONASS, and Galileo signals.

# TRIMBLE R7 GNSS SYSTEM

## PERFORMANCE SPECIFICATIONS

### Measurements

- Trimble R-Track technology
- Advanced Trimble Maxwell™ Custom Survey GNSS Chip
- High precision multiple correlator for GNSS pseudorange measurements
- Unfiltered, unsmoothed pseudorange measurements data for low noise, low multipath error, low time domain correlation and high dynamic response
- Very low noise GNSS carrier phase measurements with <1 mm precision in a 1 Hz bandwidth
- Signal-to-Noise ratios reported in dB-Hz
- Proven Trimble low elevation tracking technology
- 72 Channels:
  - GPS L1 C/A Code, L2C, L1/L2/L5 Full Cycle Carrier<sup>1</sup>
  - GLONASS L1 C/A Code, L1 P Code, L2 P Code, L1/L2 Full Cycle Carrier
- 4 SBAS WAAS/EGNOS Channels

### Code differential GPS positioning<sup>2</sup>

Horizontal . . . . . 0.25 m + 1 ppm RMS  
Vertical . . . . . 0.50 m + 1 ppm RMS  
WAAS differential positioning accuracy<sup>3</sup> . . . . . typically <5 m 3DRMS

### Static and FastStatic GPS surveying<sup>2</sup>

Horizontal . . . . . 3 mm + 0.1 ppm RMS  
Vertical . . . . . 3.5 mm + 0.4 ppm RMS

### Kinematic surveying<sup>2</sup>

Horizontal . . . . . 10 mm + 1 ppm RMS  
Vertical . . . . . 20 mm + 1 ppm RMS  
Initialization time<sup>4</sup> . . . . . typically <10 seconds  
Initialization reliability<sup>5</sup> . . . . . typically >99.9%

## HARDWARE

### Physical

Casing . . . . . Tough, lightweight, fully sealed magnesium alloy  
Dimensions (W×H×L) . . . . . 13.5 cm × 8.5 cm × 24 cm  
(5.3 in × 3.4 in × 9.5 in)

Weight . . . . . 1.5 kg (3 lb) with internal batteries, internal radio,  
internal battery charger, standard UHF antenna.  
Less than 4 kg (8.8 lb) entire RTK rover including batteries  
for 7 hours, range pole, controller and bracket

### Temperature<sup>6</sup>

Operating . . . . . -40 °C to +65 °C (-40 °F to +149 °F)  
Storage . . . . . -40 °C to +80 °C (-40 °F to +176 °F)

Humidity . . . . . 100%, condensing

Water/dustproof . . . . . IP67 dustproof, protected from temporary  
immersion to depth of 1 m (3.28 ft)

Shock and vibration . . . . . Tested and meets the following  
environmental standards:

Shock . . . . . Non-operating: Designed to survive a 1 m (3.3 ft) drop  
onto concrete. Operating: to 40 G, 10 msec, sawtooth

Vibration . . . . . MIL-STD-810F, FIG.514.5C-1

© 2007-2008, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, and TSC2 are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Integrated Surveying, Maxwell, R-Track, Trimble Survey Controller, and Zephyr Geodetic are trademarks of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. All other trademarks are the property of their respective owners. PN 022543-367B (11/09)

## Electrical

- Power input 10.5 V DC to 28 V DC with over-voltage protection
- Two rechargeable, removable 7.4 V, 2.4 Ah Lithium-Ion batteries in internal battery compartments
- Power consumption:
  - 4.0 W for receiver only (tracking and logging)
  - 4.4 W including internal radio (not receiving CMR)
  - 5.9 W (tracking SV's, logging at 1 Hz, Bluetooth<sup>®7</sup> Active, external antenna and RTK in Fixed mode)
- Operating times on internal battery:
  - >10 hours postprocessed
  - 6–8 hours RTK (with two 2.4 Ah batteries)
- Battery charger internal with external AC power adapter; no requirement for external charger
- Power output:
  - 6.5 V to 20 V (Port 1) maximum 50 mA
  - 10.5 V to 28 V (Port 3) maximum 0.5 A
- FCC Part 15C (2.4 GHz) certification, compliant with FCC Part 15B (Class B device); IC RSS-210 and RSS-310 certifications, compliant with ICES-003 (Class B device); CE-mark and C-tick mark conformity

## Communications and Data Storage

- 2 external power ports, 2 internal battery ports, 3 serial ports
- Integrated USB for data download speeds in excess of 1 megabit per second
- Fully integrated, fully sealed internal UHF radio modem option
- External cell phone support for GSM/GPRS/CDPD modems for RTK and VRS operations
- Fully integrated, fully sealed 2.4 GHz communications port (Bluetooth<sup>®7</sup>)
- 16 NMEA outputs. GSOF and RT17 output
- Dual event marker inputs
- 1 Pulse Per Second Output
- CMR+, RTCM 2.1, RTCM 2.3, RTCM 3.0, RTCM 3.1 Input and Output
- Data Storage on 256 MB CompactFlash memory at 15 second intervals:
  - 4600 hours of raw observables, GPS + GLONASS with 13 SV average
  - 8900 hours of raw observables, GPS-Only with 8 SV average

1 The availability of the L5 signal is dependent on the US Government.  
2 Accuracy and reliability may be subject to anomalies due to multipath, obstructions, satellite geometry, and atmospheric conditions. Always follow recommended survey practices.  
3 Depends on WAAS/EGNOS system performance.  
4 May be affected by atmospheric conditions, signal multipath, obstructions and satellite geometry.  
5 May be affected by atmospheric conditions, signal multipath, and satellite geometry. Initialization reliability is continuously monitored to ensure highest quality.  
6 Receiver will operate normally to -40 °C, and internal batteries are rated to -20 °C.  
7 Bluetooth type approvals are country specific. Contact your local Trimble Authorized Distribution Partner for more information.



Specifications subject to change without notice.

## NORTH AMERICA

Trimble Engineering  
& Construction Group  
5475 Kellenburger Road  
Dayton, Ohio 45424-1099 • USA  
800-538-7800 (Toll Free)  
+1-937-245-5154 Phone  
+1-937-233-9441 Fax

## EUROPE

Trimble GmbH  
Am Prime Parc 11  
65479 Raunheim • GERMANY  
+49-6142-2100-0 Phone  
+49-6142-2100-550 Fax

## ASIA-PACIFIC

Trimble Navigation  
Singapore Pty Limited  
80 Marine Parade Road  
#22-06, Parkway Parade  
Singapore 449269 • SINGAPORE  
+65-6348-2212 Phone  
+65-6348-2232 Fax

TRIMBLE AUTHORIZED DISTRIBUTION PARTNER



www.trimble.com